

64633 HLX

Low-voltage halogen lamps without reflector



Product features

- Xenon instead of krypton as the filler gas (XENOPHOT HLX versions)
- Luminous flux up to 10 % higher with same power consumption (XENOPHOT HLX versions)



Technical data

Electrical data


Light technical data

Nominal luminous flux	5600 lm
Luminous flux	5600 lm

Dimensions & weight

Diameter	11.5 mm
Filament length	3.00 mm
Light center length (LCL)	30.0 mm
Length	44.0 mm
Filament diameter	4.8 mm







Product line drawing with letters

Base

Lifespan

Additional product data

Base (standard designation)	G6.35

Capabilities


Burning position	s90

Country specific categorizations

ANSI code	BRJ
LIF	A1/234
Order reference	64633 HLX

Product datasheet







Burning position

Burning position



Logistical Data

Product code	Packaging unit (Pieces/Unit)	Dimensions (height x width x length)	Gross weight	Volume
4050300006710	Folding carton box 1	26 mm x 24 mm x 68 mm	6.00 g	0.04 dm³
4050300890616	Shipping carton box 40	121 mm x 107 mm x 144 mm	249.00 g	1.86 dm³

Product datasheet



Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.